



# Straight Abutments



A wide variety of titanium straight abutments are available for use in different situations. These abutments remain stable, even when their wall thickness is reduced to 0.1 mm. They are used in the fabrication of cement-retained restorations, single crowns or bridges.

*Recommendation: Tighten the screw at a torque between 25 to 30 Ncm.*




*Material: Titanium (Ti6Al4V ELI)*




Anatomic	Ø D (mm)	L (mm)	L1 (mm)
 NM-A4601	5.2	9	1
 NM-A4602	5.2	10	2
 NM-A4603	5.2	11	3
 NM-A4604	5.2	12	4
 NM-S8324	Included with all abutments & available separately		

L1	Ø D (mm)	L (mm)	L1 (mm)
 NM-A4801	4.5	8.5	1
 NM-A4802	4.5	9.5	2
 NM-A4803	4.5	10.5	3
 NM-A4804	4.5	11.5	4
 NM-C1005	Available separately		


Standard	Ø D (mm)	L (mm)
 NM-A5908	4.5	8.5
 NM-A5909	4.5	9.5
 NM-A5911	4.5	11.5
 NM-A5912	4.5	12.5


Shoulder, Narrow	Ø D (mm)	L (mm)	L1 (mm)
 NM-A5300	3.75	8.5	0.5
 NM-A5301	3.75	8.5	1.5
 NM-A5302	3.75	8.5	2.5

Wide	Ø D (mm)	L (mm)
 NM-A5709	5.5	9
 NM-A5711	5.5	11

Standard	Ø D (mm)	L (mm)
 NM-A5601	4.5	8.5
 NM-A5602	4.5	10.5

Narrow	Ø D (mm)	L (mm)
 NM-A6006	3.8	6
 NM-A6008	3.8	8

Mega	Ø D (mm)	L (mm)
 NM-A5515	9	15

Mega, Co-Cr	Ø D (mm)	L (mm)
 NM-A5516	15	15